



CENTRAL PENNSYLVANIA RAILROAD

THROTTLES-DT 300

THE DT 300 THROTTLE IS USED ONLY AS A LAST RESORT!

THE DT 300 THROTTLE IS A PROGRAMMING THROTTLE AS WELL AS AN OPERATING THROTTLE. IF YOU HAVEN'T BEEN TRAINED ON ITS USE, PLEASE TELL THE DISPATCHER AND DON'T ATTEMPT TO USE IT OTHER THAN SHOWN BELOW. HERE ARE SOME BASIC OPERATING PROCEDURES FOR THE DT 300. **DO NOT ATTEMPT TO PROGRAM WITH THIS THROTTLE.**

SELECTING A LOCOMOTIVE (2 digit)

1. Choose L or R knob; press or turn one quarter to activate.
2. Press select knob.
3. Turn L knob counterclockwise until 00 appears. Turn R knob until desired address appears.
4. Press select button again.
5. Blinking loco & smoke ICON indicates active throttle.

CHANGING LOCOMOTIVE DIRECTION

1. Press L or R direction key.
2. Arrow under loco icon indicates forward > or reverse < direction.
3. Alternate method-rapidly press active throttle knob twice.

ACTIVATING FUNCTIONS

1. Press function (FN) button.
2. F0, F1, F3 press button; F4 press & hold as long as needed; F5-F8 press & hold FN then press desired button.
3. Click or turn knob to exit FN mode.

DISPATCHING A LOCO OR CONSIST

1. Normal-Press SEL then MODE.
2. Consist-Press MODE MODE & when display shows MU, press N.